



40 Dale St. West Babylon, NY 11704
Ph: 631-753-9550 Fx: 631-753-9560
www.unionconnector.com

Product Bulletin No.: RMF-201

Rack Mount DistroBoxes

Features

- UL Listed
- Standard 19" EIA dimensions / mounting hole spacing
- Steel construction
- Powder coat finish.
- Variety of connectors to choose from:
 - Pin Connectors - 20 - 100A.
 - NEMA - 15 - 50A.
 - Pin & Sleeve - 20 - 100A.
 - Cam - 150 - 400A.
 - Sequential Interlock - 200 - 400A.
- Connector ratings vary from 1Ø125V., thru 3Ø 277/480V.
- Branch-rated circuit breakers.
- Indicator lights
- Color coding of wiring devices by Phase
- Custom-built to customer requirements



Options

- Meters
 - Analog- Iron Vane Ammeters; Voltmeters; Phase switches
 - Digital - Multimeter (Ammeter/Voltmeter)
- Special labelling
- Standard 19" EIA dimensions / mounting hole spacing
- Audio / Data connectors - with integral voltage barrier between Power and Data sections



Specifications

1. Units are UL Listed.
2. Enclosures are code gauge steel, finished with polyurethane paint.
3. Boxes have dimensions that conform to EIA Standards. Units shall have mounting brackets punched for standard EIA mounting hole patterns.
4. All wiring devices are UL Listed Grounding type. Where single conductor devices are used, a Grounded device shall be provided.
5. All branch circuits are provided with a UL Listed branch rated over-current protection device. .
6. All pilot lights, meters, and terminal blocks used in these boxes are UL Recognized.



40 Dale St. West Babylon, NY 11704
Ph: 631-753-9550 Fx: 631-753-9560
www.unionconnector.com

Product Bulletin No.: RMF-202

Rack Mount Panels

Features

- UL Listed
- Standard 19" EIA dimensions / mounting hole spacing
- Aluminum construction
- Powder coat finish.
- Variety of connectors to choose from:
 - Pin Connectors - 20 - 100A.
 - NEMA - 15 - 50A.
 - Pin & Sleeve - 20 - 100A.
 - Cam - 150 - 400A.
 - Sequential Interlock - 200 - 400A.
- Connector ratings vary from 1Ø125V., thru 3Ø 277/480V.
- Branch-rated circuit breakers.
- Indicator lights
- Color coding of wiring devices by Phase
- Custom-built to customer requirements



Options

- Meters
 - Analog- Iron Vane Ammeters; Voltmeters; Phase switches
 - Digital - Multimeter (Ammeter/Voltmeter)
- Special labelling
- Standard 19" EIA dimensions / mounting hole spacing
- Audio / Data connectors

Specifications

1. Units are UL Listed.
2. Panels are .125" aluminum, finished with polyurethane paint. Alternate finish is anodizing per customer color.
3. Panels have dimensions that conform to EIA Standards. Units shall have mounting brackets punched for standard EIA mounting hole patterns.
4. All wiring devices are UL Listed Grounding type. Where single conductor devices are used, a Grounded device shall be provided.
5. All branch circuits are provided with a UL Listed branch rated over-current protection device. .
6. All pilot lights, meters, and terminal blocks used in these panels are UL Recognized.