

Rack Mount DistroBoxes

Features

- UL Listed
- Standard 19" EIA dimensions / mounting hole spacing
- Steel construction
- Powder cost finish.
- Variety of connectors to choose from:

Pin Connectors - 20 - 100A.

NEMA - 15 - 50A.
Pin & Sleeve - 20 - 100A.
Cam - 150 - 400A.
Sequential Interlock - 200 - 400A.

- Connector ratings vary from 1Ø125V., thru 3Ø 277/480V.
- Branch-rated circuit breakers.
- Indicator lights
- Color coding of wiring devices by Phase
- Custom-built to customer requirements



Options

- Meters
 - Analog- Iron Vane Ammeters; Voltmeters; Phase swithes Digital Multimeter (Ammeter/Voltmeter)
- Special labelling
- Standard 19" EIA dimensions / mounting hole spacing
- Audio / Data connectors with integral voltage barrier between Power and Data sections



Specifications

- 1. Units are UL Listed.
- 2. Enclosures are code gauge steel, finished with polyurethane paint.
- 3. Boxes have dimensions that conform to EIA Standards. Units shall have mounting brackets punched for standard EIA mounting hole patterns.
- 4. All wiring devices are UL Listed Grounding type. Where single conductor devices are used, a Grounded device shall be provided.
- 5. All branch circuits are provided with a UL Listed branch rated over-current protection device. .
- 6. All pilot lights, meters, and terminal blocks used in these boxes are UL Recognized.

RMF-201B-1