

Outdoor Company Switch

60A., 120/208V., Series 16 Cams and Connection Chamber



- Electric power distribution center for theatre, convention centers, arenas, schools, churches, and events centers
- Series 16 Cam receptacles
- Color-coded snap-back covers
- 60A. Main breaker rated 65K AIC
- Connection chamber for bare-end cables. Door is electrically interlocked with main breaker shunt trip
- Outdoor rated Type 3R enclosure
- Options:
 - ✦ Reverse Neutral/Ground
 - ✦ Parallel sets of receptacles
 - ✦ Isolated Ground
 - ✦ 1Ø - 120V., 120/240V.,
 - ✦ 3Ø - 277/480V., 208V., 480V.
 - ✦ Digital Meter
 - ✦ Custom color finish
 - ✦ Recessed or Pad mounting
 - ✦ Type 4 or 4X enclosure

- Catalog Number:** CSC-0610-CSP-3R
- Product Type:** Company Switch with Series 16 Cam receptacles and connection chamber
- Main Enclosure:** TYPE 3R, Galvanized Steel, ANSI 61 Gray powder-coat finish, wall mounting brackets, door for portable cable on bottom of enclosure
- Dimensions:** 40"H. x 24"W. x 10" D.
- Rating:** 60A., 120/208V., 3Ø, 4W+G
- Circuit Breakers:** Molded-case, UL489, 65K AIC @ 240V., (1) 60A., 3-pole
- Receptacles:** (5) Series 16 Cam panel mount color coded receptacles with snap-back protective covers.
- Busbar Output:** (5) dual rated mechanical lugs on copper bus accessible in connection chamber
- Monitoring:** LED Indicator lights to indicate presence of phase voltage.
- Labelling:** Laser engraved cam identifiers and panel rating. Cable connection warning label per NEC Art 520.
- Listing:** UL Listed