

# Outdoor Company Switch

60A., 120/208V., Series 16 SafeCam® and Connection Chamber



- Electric power distribution center for theatre, convention centers, arenas, schools, churches, and events centers
- Series 16 SafeCam® receptacles
- 60A. Main breaker rated 65K AIC containing an integral shunt trip
- SafeCam® system monitors receptacles and activates shunt trip whenever a plug is disconnected from a receptacle
- Connection chamber for bare-end cables. Door is electrically interlocked with main breaker shunt trip
- Outdoor rated Type 3R enclosure
- Options:
  - ✧ Reverse Neutral/Ground
  - ✧ Parallel sets of receptacles
  - ✧ Isolated Ground
  - ✧ 1Ø - 120V., 120/240V.,
  - ✧ 3Ø - 277/480V., 208V., 480V.
  - ✧ Digital Meter
  - ✧ Custom color finish
  - ✧ Recessed or Pad mounting
  - ✧ Type 4 or 4X enclosure

**Catalog Number:** CSC-0610-SCSP-3R

**Product Type:** Company Switch with Series 16 SafeCam® receptacles and connection chamber

**Main Enclosure:** TYPE 3R, Galvanized Steel, ANSI 61 Gray powder-coat finish, wall mounting brackets, door for portable cable on bottom of enclosure

**Dimensions:** 40"H. x 24"W. x 10" D.

**Rating:** 60A., 120/208V., 3Ø, 4W+G

**Circuit Breakers:** Molded-case, UL489, 65K AIC @ 240V., (1) 60A., 3-pole

**Receptacles:** (5) Series 16 SafeCam® panel mount color coded receptacles with snap-back protective covers.

**Busbar Output:** (5) dual rated mechanical lugs on copper bus accessible in connection chamber

**Monitoring:** LED Indicator lights to indicate presence of phase voltage.

**Labelling:** Laser engraved cam identifiers and panel rating. Cable connection warning label per NEC Art 520.

**Listing:** UL Listed

Union Connector Co., Inc.  
Jacksonville, FL 32256  
631-753-9550

