

# Company Switch

400A., 120/208V., Series 16 Cams and Connection Chamber



- Electric power distribution center for theatre, convention centers, arenas and events centers
- Series 16 Cam receptacles
- Color-coded snap-back covers
- 400A. Main breaker rated 65K AIC
- Connection chamber for bare-end cables. Door is electrically interlocked with main breaker shunt trip
- Options:
  - ✧ Reverse Neutral/Ground
  - ✧ Parallel sets of receptacles
  - ✧ Isolated Ground
  - ✧ 1Ø - 120V., 120/240V.,
  - ✧ 3Ø - 277/480V., 208V., 480V.
  - ✧ Digital Meter
  - ✧ Custom color finish
  - ✧ Recessed or Pad mounting
  - ✧ Type 3R, 4 or 4X enclosure

- Catalog Number:** CSC-4020-CSP
- Product Type:** Company Switch with Series 16 Cam receptacles and connection chamber
- Main Enclosure:** TYPE 1, Steel, black wrinkled powder-coat finish, wall mounting brackets .Hinged access door to connection chamber, with lockable handle. Electrical interlock on door shall activate shunt trip in breaker when door is opened.
- Cable Entry:** Grommeted holes in bottom of enclosure for portable bare-end cable entry.
- Dimensions:** 42"H. x 21"W. x 8¾" D.
- Rating:** 400A., 120/208V., 3Ø, 4W+G
- Circuit Breakers:** Molded-case, UL489, 65K AIC @ 240V.,  
(1) 400A., 3-pole with shunt trip interlocked with connection chamber door
- Receptacles:** (6) Series 16 Cam (Dual Neutral) panel mount color coded receptacles with snap-back protective covers.
- Busbar Output:** (6) dual rated mechanical lugs on copper bus accessible in connection chamber
- Monitoring:** LED Indicator lights to indicate presence of phase voltage.
- Labelling:** Laser engraved cam identifiers and panel rating. Cable connection warning label per NEC Art 520.
- Listina:** UL Listed

Union Connector Co., Inc.  
Jacksonville, FL 32256  
631-753-9550

